

GENERAL PURPOSE TOOLS



SEDRA MARINE

FRANCE

Tél. : + 33 (0) 5 62 28 32 52 - Fax : + 33 (0) 5 62 28 40 68
e-mail : info@sedra-marine.fr - Site : <http://www.sedramarine-ard.com>



GENERAL PURPOSE TOOLS

Levels



Torpedo Levels

Ideal for general use and work in tight places. Three vials for plumb, level, and 45° miter. Made of heat treated aluminum with plastic insert. Model No. 390 is grooved for pipe, conduit, and shaft work. Model No. 390M is magnetized for metal work and easy storage.

Magnetic Protractor Level

Magnetic edge frees hands when working with metal. Angle reference. Protractor measures angles accurately. Transfers angles to within 30 seconds of arc, same rugged precision construction as other aluminum levels.

Magnetic Aluminum Level

Rust and warp-proof extruded aluminum, milled to close tolerances for accurate leveling (accuracy 0.5 mm per metre). Very light weight. Magnetic edge for metal work.

Variable Pitch Level

Leading edge of variable pitch bubble indicates from "level" to 1/2 inch per foot pitch or slope. No screws or protractor to adjust. Frame is high alloy heat treated aluminum. Precision milled surface. Replaceable vials. Ideal for plumbing, pipe fitting, carpentry, masonry, excavation and where slope or drainage is a consideration.

Line Level

Locks on cord easily, releases easily. Flat base for surface leveling. Accurate, pre-tested vial.

Catalog No.	Model No.	Description	Length		Body		Weight kg	Std. Pack
			in.	mm	in.	mm		
66762	880M	22 cm magnetic, laser level	9	220	3/4 x 1 3/4	19 x 46	0,3	1
88225	648A	48" aluminum, top read level	48	1219	1 x 2 3/16	25 x 56	1,8	1
96365	624VP	24" aluminum, variable pitch level	24	610	1 x 2 3/16	25 x 56	1,0	1
36547	618VP	18" variable pitch level	18	45	1 x 2 3/16	25 x 56	0,5	1
36557	624PRO	24" magnetic protractor level	24	610	1 x 2 3/16	25 x 56	0,6	1
36552	618PRO	18" magnetic protractor level	18	458	1 x 2 3/16	25 x 56	0,5	1
36125	390	9" torpedo level	9	229	5/8 x 1 1/4	16 x 32	0,8	6
36130	390M	9" torpedo, magnetized level	9	229	5/8 x 1 1/4	16 x 32	0,8	6
36120	325L	3 1/4" line level	3 1/4	83	7/16 Hex	11 Hex	0,1	6
20161	640M	40 cm magnetic, aluminum level	16	400	1 x 2 3/16	25 x 56	0,4	10
20171	660M	60 cm magnetic, aluminum level	24	610	1 x 2 3/16	25 x 56	0,6	10
20181	680M	80 cm magnetic, aluminum level	32	800	1 x 2 3/16	25 x 56	0,7	10

GENERAL PURPOSE TOOLS

Extractors / Twist drills

Screw extractors
(with sliding turnut)



Catalog No.	Mod No.	Screw Diameter		Use drill		Flute Diameter		Length Overall		Max. Depth		Wt. g	Std. pack
		in.	mm	in.	mm	in.	mm	in.	mm	in.	mm		
35535	1	1/4	6	1/8	3	0.139	3,5	2 5/16	59	1	25	14	1
35540	2	5/16	8	3/16	5	0.205	5,2	2 3/4	70	1	25	28	1
35545	3	3/8	9,5	1/4	6	0.272	6,9	3 1/16	78	1	25	35	1
35550	4	7/16	11	5/16	8	0.338	8,6	3 5/16	84	1	25	50	1
35555	5	1/2-9/16	13-14	11/32	9	0.374	9,5	3 3/4	95	1	25	64	1
No turnut													
35560	6	5/8	16	7/16	11	0.471	12,0	4 1/8	105	2	51	85	1
35565	7	3/4	19	1/2	13	0.538	13,7	4 1/2	114	2	51	113	1
35570	8	7/8-1	22-25	5/8	16	0.665	16,9	4 3/4	121	3	76	184	1



Screw Extractors (In Sets)

Catalog No.	Model No.	Description	Wt. g	Std. Pack
35575	3	Includes Nos. 3, 4 and 5	227	1
35580	5	Includes Nos. 1, 2, 3, 4 and 5	227	1

No. 10 Screw Extractor Set

No. 10 set contains 20 precision tools - one each of Extractor Nos. 1 to 5 inclusive, turnuts, drills No. 1 to 5 inclusive, and drill guides Nos. 921 to 1821 inclusive. Pre-formed plastic box provides convenient storage.

Catalog No.	Model No.	Description	Capacity		Wt. kg	Std. Pack
			in.	mm		
35585	10	Screw extractor Set	1/4-1/2	6-13	0,6	1



No. 25 Screw and Pipe Extractor Set

No. 25 set contains one each of screw extractors Nos. 1 to 8 inclusive (Nos. 1 to 5 Extractors with turnuts) ; Drill Nos. 1 to 8 inclusive, and No. 36 ; and complete set of drill guides and bushings. Maximum depth extractor range 1" to 3". Pipe extractors Nos. 80 to 85 also included. These precision tools are packed in a fitted compartment box.

Catalog No.	Model No.	Description	Capacity			Wt. g	Std. Pack
			Type	in.	mm		
35590	25	Pipe and screw Extractor set	Screw Pipe	1/4-1 1/8-1	6-25 3-25	4,2	1



Replacement Drill Guides
(One-piece Type)

Catalog No.	Model No.	Diam. O.D.		Overall length		Use Drill		Wt. g	Std. Pack
		in.	mm	in.	mm	in.	mm		
35765	921	9/32	7,1	1 3/16	30	1/8	3	7	1
35770	1021	5/16	7,9	1 3/16	30	1/8	3	14	1
35775	1121	11/32	8,7	1 3/16	30	1/8	3	14	1
35780	1221	3/8	9,5	1 3/16	30	1/8	3	14	1
35785	1321	13/32	10,0	1 3/16	30	3/16	5	14	1
35790	1421	7/16	11,1	1 3/16	30	3/16	5	21	1
35795	1521	15/32	11,9	1 3/16	30	3/16	5	21	1
35800	1621	1/2	12,7	1 3/16	30	3/16	5	28	1
35805	1721	17/32	13,5	1 3/16	30	1/4	6	28	1
35810	1821	9/16	14,3	1 3/16	30	1/4	6	28	1



High-Speed Twist Drills

Catalog No.	Model No.	Diam. O.D.		Overall length		Wt. g	Std. Pack
		in.	mm	in.	mm		
35720	1	1/8	3	2 1/2	63	7	1
35725	2	3/16	5	3	73	14	1
35730	3	1/4	6	3 1/2	89	21	1
35735	4	5/16	8	4	102	35	1
35740	5	11/32	9	4 1/2	114	43	1
35745	6	7/16	11	4 3/4	121	71	1
35750	7	1/2	13	5	127	99	1
35755	8	5/8	16	5 1/2	139	156	1
35760	36	1/4	6	6	152	43	1